



NOEPOX

CLEANER FOR THE REMOVAL OF EPOXY GROUT RESIDUES



User guide

DESCRIPTION:

Thickened mixture of organic solvents. Contains no CFC.

FIELDS OF APPLICATION:

On all surfaces in porcelain tiles, glazed ceramics, glass mosaics. Can be used for cleaning compact stone materials (e.g. granites, quartzites, etc.). Can be used both indoors and outdoors.

CHARACTERISTICS:

NOEPOX is a specific solvent cleaner for the removal of epoxy grouts from stone materials.

NOEPOX:

- eliminates the hardened residues of the epoxy grouts on the tile surface, without causing corrosion or discoloration of the already hardened plaster by the joint;
- is neither alkaline nor acid, therefore can be used safely even in the presence of stone surfaces;
- can be applied on all stone materials such as cotto, stone, glazed ceramics, klinker, porcelain tiles, cement, grits, etc, and also on wood, glass, metals and plastic;
- thanks to its viscosity, can be easily used on vertical surfaces.

INSTRUCTIONS FOR USE:

- It is used pure;
- Wait at least 24 hours after grouting before using NOEPOX;
- Always apply on dry surface;
- Spread the product with a brush on the surface to be cleaned;
- Proceed a few square meters at a time;
- Leave to act for about 30-60 minutes on the dried residues of plaster, 2-4 hours or more on the hardened residues of plaster;
- Then rinse with water (preferably with 1:10 UNIPUL aqueous detergent solution) rubbing the surface with a nylon brush or brown buffer proceeding diagonally with respect to the joints. On large surfaces and floors it is possible to intervene with a monobrush equipped with a brown disc;
- Finally rinse again with water.

PRECAUTIONS:

- do not use on synthetic polymers (e.g. synthetic agglomerates, methacrylate) and wood;
- avoid contact with plastic surfaces, paints and varnishes. On metal surfaces check their suitability.

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. Rev4-Ver110222

WARNINGS:



WARNINGS: DANGER

Hazard statements: Causes serious eye irritation. – May cause an allergic skin reaction.

Precautionary statements: Wear protective gloves/eye protection/face protection. – Avoid breathing dust/fume/gas/mist/vapours/ spray. -If skin irritation or rash occurs: Get medical advice/attention. -If eye irritation persists: Get medical advice/ attention. -Take off contaminated clothing and wash it before reuse.

Contains: BENZYL ALCOHOL

UFI: F610-105N-C00G-XWYK

Rev5-Ver130225

PACKAGING:

- 1 lt conf. Can – box 6 pcs.

YIELD:

- to remove the dried residues (after about 1-2 days.) 1lt / 15-20 m2;
- to remove the hardened residues (after 2-3 days.) 1lt / 10-15 m2.

TECHNICAL DATA:

- Physical state: colorless dense liquid
- Specific gravity (g/cm3) at 20°C: 1.09
- pH: n.a.
- Flame point (ASTM): > 90°C
- Solubility in water: insoluble in water.

STORAGE:

Keep the product tightly closed and at a temperature between 5 and 30 °C and not exposed to sunlight for a long time. STORAGE PERIOD: 5 years.

MARBEC SRL

CUSTOMER SERVICE

Via Croce Rossa 51
51037 - Montale PT
Italia

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it