TIXO®

STAIN REMOVER FOR OIL AND GREASE STAINS OF NATURAL ORIGIN

User guide

DESCRIPTION:

Thickened alkaline dispersion based on inorganic alkali, solvents, imbibing surfactants and micro-porous mineral thickener.

FIELDS OF APPLICATION:

Specific stain remover for stone materials such as: cotto, stone, glazed and unglazed ceramic, klinker, porcelain tiles, cement, grit, etc.

CHARACTERISTICS:

TIXO is a strong thickened alkaline-solvent stain remover, specific for removing oil and grease stains of natural origin on all stone materials (e.g. cotto, stone, porcelain tiles, ceramic, cement and cement joints).

TIXO:

– removes grease stains of vegetable or animal origin, dry oils (e.g. flax oil and wood), deposits of encrusted and penetrated grease;
– is ideal where there is a need for long extraction times (stains deeply penetrated into the porosity of the material);
– thanks to the special microporous thickening material, the action of the product can be suitably and easily prolonged in time;
– can also be used to remove carbon black or soot from fireplaces, from stone materials;
– does not leave harmful residues in the absorbent material;
– leaves no unpleasant odors during use and in environments.

INSTRUCTIONS FOR USE:

– Mix well before use;
– Proceed with the application of the product with a spatula taking care to leave a layer of at least 3-5 mm of TIXO on the stain to be removed;
– If necessary, the duration of the extractive action can be increased by covering the compress with a sheet of plastic material (kitchen film) in order to slow the evaporation;
– Always allow the pack to dry and then proceed to its dry removal with a nylon brush;
– Finally, rinse with acid solution of DELICACID diluted 1:10 in water or with neutral solution of UNIPUL diluted 1:3 in water on delicate materials (e.g. marble, polished grit);
– Repeat the application if necessary.

On treated surfaces, the application of TIXO, being a strong alkaline stain remover, removes any treatments (wax or resin). It is advisable to apply the product not only on the defined stain, but on all the affected tile or step so as to have a uniform surface and without halos.

PRECAUTIONS:

– protect painted surfaces, anodised aluminium and wood surfaces from contact with TIXO;
– not to use plant or animal equipment;
– always test before use;
– if used outdoors, it is advisable to avoid spreading the product on too hot and exposed to the sun.

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products.
Rev5-Ver310122

WARNINGS:

WARNING: DANGER

Hazard statements: Causes severe skin burns and eye damage.

Precautionary statements: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. – IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. – Wear protective gloves/ protective clothing / eye protection / face protection. – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. -IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Contains: SODIUM HYDROXIDE, Dodecyl benzene sulfonic acid

Ingredients compliant with Regulation (EC) No. 648/2004:
Anionic surfactants <5%

UFI:TX00-H03F-F000-XW7D

Rev5-Ver310122

PACKAGING:

– 1 Kg plast. Tin – box 6 pcs;
– 5 Kg plast. Bucket – box 4 pcs.

YIELD:

Depending on the dirt to be removed and the absorption of the material. On average 1lt/ 1 -2 sqm each hand.

TECHNICAL DATA:

Physical state: Avana mushy liquid
Specific gravity: = 1,06 kg/l
pH: 14
Flame point: > 60 ºC
Solubility in water: partial

STORAGE:

Keep the product well closed out of reach of children and in a well ventilated and cool environment, not exposed for a long time to sunlight. Storage period: 5 years

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it