



POLIFIN

METALLIZED WAX WITH A GLOSSY ANTI-DIRT FINISH, ANTI-WEAR FOR STONE MATERIALS



User guide

DESCRIPTION:

O/A emulsion based on acrylic emulsions and mineral waxes.

FIELDS OF APPLICATION:

For the final glossy finish of the absorbent stone materials placed inside: cotto, natural stones, grits, cements, klinker especially on those with polished finish. Also suitable for resilient materials (PVC, linoleum, resin floors).

CHARACTERISTICS:

POLIFIN is a shiny metallic wax for stone materials placed inside: cotto, natural stone absorbent, terrazzo. Also suitable for resilient materials (PVC, linoleum, resin floors).

POLIFIN:

- is a water based product, not dangerous and easy to use;
- is strongly recommended at the end of the treatments with hydro-oleophobic protective, oily-waxy impregnations, leveling primers, as it protects the surfaces from the wear of time and prevents the degradation of the bottom treatment;
- makes a micro-waxy resin layer on the material, easy to apply, which reduces dirt penetration and makes the surfaces easier and faster to clean;
- leaves a good vapor permeability to the material;
- is easy to apply and maintain over time.

In maintenance it is advisable to clean the surface treated with UNIPUL detergent and to apply POLIFIN wax once every 6-12 months depending on the floor trampling.

INSTRUCTIONS FOR USE:

It is normally used pure.

- Apply on clean and dry surfaces;
- Shake before use;
- Apply the product in small quantities of product on the surface and distribute with a soft cloth, spreading fleece and evenly on the surface;
- Do not step on the product during drying;
- Apply the second coat as soon as the first coat is dry;
- To increase the gloss after drying or to remove tread marks, rub the surface treated with a wool cloth, polisher with felt, red buffers, single brush with red discs.

It generally dries in 2-3 hours.

Types of application:

- 1 coat: on smooth and slightly absorbent surfaces;
- 2 hands: on rough surfaces.

PRECAUTIONS:

- avoid applying by brush or roller. Do not use outside;
- avoid the application of POLIFIN on too cold surfaces ($< 5^{\circ}\text{C}$);
- avoid, when cleaning surfaces treated with POLIFIN, the use of strong alkaline and acid detergents (e.g. ammonia, sodium hypochlorite, various acids) and solvents (e.g. ethyl alcohol).

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the

WARNINGS:

WARNING: DANGER

Hazard statements: Causes serious eye damage. – Contains: Rosin acids, fumarates, esters with pentaerythritol and mixture of 5-chloro-2methyl-2H-isothiazol-3-one and 2methyl-2H-isothiazol-3-one. – May produce an allergic reaction.

Precautionary statements: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. – Wear eye protection / face protection. – Immediately call a POISON CENTER / doctor / . . .

Contains: Alcohols, branched and linear C12-15, ethoxylated ($\geq 7 - <15$ EO)

VOC (Directive 2004/42 / EC): High performance one-component paints.

VOC expressed in g / liter of ready-to-use product: 40,00. – Maximum limit: 140,00

UFI:3K50-U0CV-Y00R-NAPV

Rev7-Ver020222

PACKAGING:

- 1 lt Plastic bottle- box 6 pcs;
- 5 lt Plastic tank- box 4 pcs.

YIELD:

Depending on the absorption of materials:

- on materials with rough surfaces 1 lt /15-18 m²;
- on materials with smooth surfaces 1 lt / 25-50 m².

TECHNICAL DATA:

- Physical state: white liquid
- Specific gravity (g/cm³): 1,01
- pH: 8 – 9.
- Flame point (ASTM): non-flammable
- Solubility in water: soluble in water
- Drying time: 2 – 3 hours
- Consolidation time: 24 hours

STORAGE:

Keep the product tightly closed at temperatures between 0 °C and +30 °C and not exposed to sunlight for a long time. The stored product has a useful life of 2 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it