




KW L

LIQUID CRYSTALLISER FOR STONES, MARBLE AND POLISHED LIMESTONE MATERIALS



User guide

DESCRIPTION:

Crystallizing liquid based on acid salts, surfactants, glycols.

FIELDS OF APPLICATION:

For polishing stones containing calcium carbonate, such as: marble, travertine, limestone agglomerates.

CHARACTERISTICS:

KW-L is a crystallizing liquid product for the polishing of stones containing calcium carbonate, such as marble, travertine, limestone agglomerates.

KW-L:

- is a product for the periodic polishing and maintenance of high traffic surfaces that have lost their original brilliance;
- can be used for final polishing after sanding with traditional systems;
- facilitates the cleaning and maintenance of treated surfaces.

INSTRUCTIONS FOR USE:

KW-L is ready to use.

Apply only on clean, dry and untreated floors.

- Shake before use;
- Spray KW-L by spraying it on the surface and immediately work with a single brush equipped with STAINLESS STEEL WOOL DISC until the product is completely absorbed and the floor is polished;
- Treat 1-2 m² at a time. For a greater brilliance, proceed with a first crystallization with a disc in coarse steel wool and then recrystallize with a disc in fine steel wool;
- Leave for a few hours and rinse with water and neutral detergent (e.g. UNIPUL). For a better shine, polish the floor with a clean STAINLESS STEEL WOOL DISC or WHITE DISC.

PRECAUTIONS:

- avoid pouring KW-L directly onto the surface;
- do not use rusted steel wool discs;
- use only on limestone stones;
- avoid other materials.

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products.
Rev5-Ver150222

WARNINGS:



WARNING: DANGER

Hazard statements: Harmful if swallowed. – Causes serious eye damage.

Precautionary statements: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. – Wear eye protection / face protection. – Immediately call a POISON CENTER / doctor / . . . – Wash . . . thoroughly after handling. – Rinse mouth.

Content: Magnesium hexafluorosilicate hexahydrate, acetic acid.

PROFESSIONAL USE

UFI: P770-F0GE-T004-7TS3

Rev5-Ver150222

PACKAGING:

- 1 lt Pe bottle box 6 pcs;
- 5 lt Can of Pe box 4 pcs.

YIELD:

Depending on the nature of the stone to be treated:

- in periodic maintenance: 1lt / 40-60 m²;
- on very worn surfaces: 1 lt / 10-30 m².

TECHNICAL DATA:

- Physical state: white liquid
- Specific gravity (g/cm³): 1,09
- pH (20 ?? C) of the pure product: 1
- Flame point (ASTM): > 90°C
- Solubility in water: soluble in water.

STORAGE:

Keep the product tightly closed at temperatures between 0 °C and +30 °C and not exposed to sunlight for a long time. The stored product has a useful life of 2 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it