



REFIX LUCIDO

GLOSS MAINTENANCE WAX FOR INDOOR TERRACOTTA AND NATURAL STONE



User guide

DESCRIPTION:

O/A emulsion based on vegetable waxes, mineral waxes and resins.

FIELDS OF APPLICATION:

Suitable for the periodic maintenance of previously treated, absorbent stone-based surfaces finished with emulsions such as IDROFIN and located indoors, including:

- terracotta;
- absorbent natural stone;
- cement-based agglomerates.

CHARACTERISTICS:

REFIX LUCIDO is a gloss maintenance wax for already treated, absorbent mineral surfaces indoors, such as terracotta, natural stone and cement-based agglomerates. In particular:

- it has a water-based formula that is easy to use and is not classified as hazardous;
- it helps preserve the protective and aesthetic properties of the original gloss finish over time;
- it renews the surface protection affected by normal wear;
- it makes treated surfaces easier to clean and maintain;
- it maintains the appearance of the gloss finish without forming a film or coating;
- its self-levelling properties help the product spread evenly over the surface;
- once dry, it can be dry polished to increase and maintain the surface gloss and remove marks caused by foot traffic;
- it leaves a pleasant fragrance in the room.

INSTRUCTIONS FOR USE:

REFIX LUCIDO should be applied to clean and completely dry surfaces. Before use, shake the product well to ensure an even distribution of the maintenance wax.

- Apply the product in small amounts to the surface to be maintained.
- Spread it evenly with a soft cloth or a wax applicator.
- Allow the product to dry and do not walk on the surface during the drying process.

The product has an approximate drying time of 30–60 minutes and reaches full curing in about 2 hours.

Dry Polishing

Once dry, REFIX LUCIDO can be dry polished to increase and maintain the surface gloss or to remove marks caused by foot traffic. For polishing, use:

- a wool cloth;
- a floor polisher with felt pads;
- red hand pads;
- a single-disc floor machine with red discs.

How often REFIX LUCIDO should be applied depends on foot traffic and surface wear:

- Every 4–6 months on heavily trafficked surfaces subject to significant wear, such as shops, public premises, bars, restaurants, kitchens, entrances and bathrooms.
- Every 12 months on surfaces with limited foot traffic, such as bedrooms and living rooms.

PRECAUTIONS:

To preserve the properties of the finish maintained with REFIX LUCIDO over time:

- avoid using strongly alkaline cleaners;
- avoid using ammonia-based cleaners;

- do not use solvents to clean treated surfaces.

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products.
Rev4-Ver060422

WARNINGS:

Hazard statements: safety data sheet available on request.

Rev4-Ver060422

PACKAGING:

- 1 L plastic bottle – boxes of 6 units
- 5 L plastic container – boxes of 4 units

YIELD:

The coverage of REFIX LUCIDO varies depending on the surface finish of the material. As a guide, 1 litre covers approximately 30–40 m².

TECHNICAL DATA:

- Physical state: white liquid
- Specific gravity (g/cm³): 1,00
- pH: 8
- Flame point (ASTM): > 90°C
- Solubility in water: soluble in water
- Drying time: 30 – 60 minutes
- Consolidation time: 2 hours

STORAGE:

Keep the product tightly closed at temperatures between 0 °C and +30 °C and not exposed to sunlight for a long time.

STORAGE PERIOD: The product thus preserved has a useful life of 2 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it