



REFIX MATT

MATT MAINTENANCE WAX FOR INDOOR TERRACOTTA AND NATURAL STONE



User guide

DESCRIPTION:

FIELDS OF APPLICATION:

Suitable for the periodic maintenance of previously treated, absorbent stone-based surfaces finished with emulsions such as IDROFIN and located indoors, including:

- terracotta;
- absorbent natural stone;
- cement-based agglomerates.

CHARACTERISTICS:

REFIX MATT is a matt maintenance wax for previously treated, absorbent stone-based materials, such as terracotta, natural stone and cement-based agglomerates located indoors. In particular:

- it has a water-based formula, is easy to use and is not classified as hazardous;
- it preserves the protective and aesthetic properties of the original matt finish over time;
- it renews the surface protection of the treatment affected by normal wear;
- it makes treated surfaces easier to clean and maintain;
- it maintains the matt appearance of the finish without creating glossy films or layers;
- it is a self-levelling wax that helps distribute the product evenly over the surface;
- it leaves a pleasant scent in the room.

INSTRUCTIONS FOR USE:

Apply REFIX MATT to clean and completely dry surfaces. Shake the product well before use to help distribute the maintenance wax evenly.

- Apply the product in small amounts to the surface that requires maintenance.
- Spread it evenly using a soft cloth or a wax applicator.
- Allow the product to dry and do not walk on the surface during the drying process.

The product has an approximate drying time of 30–60 minutes and reaches full consolidation in about 2 hours.

How often you should apply REFIX MATT depends on foot traffic and surface wear:

- Every 4–6 months on heavily used surfaces exposed to greater wear, such as shops, public premises, bars, restaurants, kitchens, entrances and bathrooms.
- Every 12 months on surfaces with low foot traffic, such as bedrooms and living rooms.

PRECAUTIONS:

To preserve the properties of the finish maintained with REFIX MATT over time:

- avoid using strongly alkaline cleaners;
- avoid using ammonia-based cleaners;
- do not use solvents to clean treated surfaces.

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products.

Rev5-Ver060422

WARNINGS:

PACKAGING:

- 1 L plastic bottle – boxes of 6 units
- 5 L plastic container – boxes of 4 units

YIELD:

The coverage of REFIX MATT varies depending on the surface finish of the material. As a guide, 1 litre covers approximately 30–40 m².

TECHNICAL DATA:

- Physical state: pink liquid
- Specific gravity (g/cm³): 1.00
- pH: 8
- Flash point (ASTM): > 90 °C
- Water solubility: soluble in water
- Drying time: 30–60 minutes
- Full consolidation time: 2 hours

STORAGE:

Store the product tightly closed at temperatures between 0 °C and +30 °C. Do not expose it to sunlight for prolonged periods. STORAGE LIFE: When stored under these conditions, the product has a shelf life of 2 years.