



DELUXE TEAK

STAIN REMOVER FOR BOAT DECKS AND TEAK SURFACES



User guide

DESCRIPTION:

Mixed acid/solvent solution with low foaming surfactants.

FIELDS OF APPLICATION:

For extraordinary washing and specific renewal of wood surfaces exposed outdoors in a marine environment.

CHARACTERISTICS:

DELUXE TEAK is a teak boat cleaner with low foaming, specific for wood exposed outdoors in a marine environment.

DELUXE TEAK:

- removes natural aging patinas caused by sun exposure.
- eliminates marine-origin algae, mold, and salt deposits.
- restores the natural appearance of aged wood, giving it a refreshed look and preparing it for a new protective treatment (such as oils or wood sealers).
- eliminates the need for sanding.
- is easy and quick to apply.

INSTRUCTIONS FOR USE:

- Shake before use;
- Apply the product with a brush, cloth or sponge, wetting the surface thoroughly;
- Keep the surface wet for 20 – 30 minutes;
- Then rub **DELUXE TEAK** with blue buffers or nylon brushes, following the wood grain;
- Finally, rinse thoroughly with plenty of water and allow to dry;
- Repeat the application if necessary.

DELUXE TEAK is not a paint stripper, nor a stripper and does not remove paint layers, impregnations, oils and waxes.

PRECAUTIONS:

- always test before use,
- do not apply to too hot surfaces;
- protect the eyes and skin from contact with the product in appropriate clothing.

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products.
Rev5-Ver170222

WARNINGS:



WARNING: DANGER

Indications of danger: Causes severe eye burns.

Precautionary statements: Protect the eyes/ face. – IN CASE OF CONTACT WITH EYES: rinse thoroughly for

several minutes. Remove any contact lenses if it is easy to do so. Immediately contact a POISON CENTER/ a doctor/...

Contains: oxalic acid bihydrate

UFI: 7630-P01S-D00V-4SD2

Rev5-Ver170222

PACKAGING:

- 1 lt Pe bottle – box 6 pieces;
- 5 lt Pe tank – box 4 pieces.

YIELD:

- Depending on the dirt to be removed and the absorption of the material.

TECHNICAL DATA:

- Physical state: colourless liquid
- Specific Gravity (20°C): 1.035
- pH (20°C): 2
- Flame point (ASTM): > 90°C
- Solubility in water: soluble in water

STORAGE:

Keep the product tightly closed and at a temperature between 5 and 30 °C in an aerated environment, away from heat sources and not exposed to sunlight for a long time. When stored at low temperatures (<10 °F) the product can become dense, but without affecting its use or performance. The stored product has a useful life of 5 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it