



LIGNOLIFE®

FINISH FOR RESTORING GLOSS VARNISHED PARQUET



User guide

DESCRIPTION:

Water-based resin-wax finish for restoring gloss varnished parquet and indoor varnished wood surfaces. Restores shine, protects the existing varnish and improves its resistance to everyday wear.

FIELDS OF APPLICATION:

LIGNOLIFE® is recommended for:

- gloss varnished parquet;
- gloss varnished wood wall coverings;
- gloss varnished wooden furniture;
- gloss varnished interior doors and window frames.

CHARACTERISTICS:

LIGNOLIFE® is a water-based resin-wax finish formulated with carnauba wax, specifically developed to restore gloss varnished parquet and indoor varnished wood surfaces.

LIGNOLIFE®:

- is easy to apply;
- is recommended for restoring dull and worn gloss varnished parquet and indoor varnished wood surfaces;
- restores colour and provides a renewed gloss finish;
- forms a new protective film that improves the varnish's resistance to foot traffic, dirt, water and household detergents;
- is self-polishing and does not require mechanical polishing;
- is easy to maintain with routine cleaning using PULIBRILL® and by applying BEAUTY FLOOR every 6–12 months.

LIGNOLIFE® is not a substitute for re-varnishing where the original varnish has been completely worn away. If the wood is exposed, for example in grey worn areas or where water is directly absorbed into the wood, the surface must first be restored by re-varnishing.

INSTRUCTIONS FOR USE:

Before applying LIGNOLIFE®, carry out a deep cleaning treatment using PULIBRILL® and a WHITE PAD to remove dirt and residues that could affect the adhesion of the product.

- Shake well before use.
- Apply 2 coats of LIGNOLIFE® using a wax applicator fleece, microfibre cloth or sponge.
- Apply the product in a thin, even coat, ensuring complete and uniform coverage without leaving excess material on the surface.
- Apply the second coat as soon as the first coat is dry.
- Allow the treatment to dry. Under normal conditions and in a well-ventilated area, the product dries in approximately 2–3 hours.

Do not apply the product to cold surfaces (below 7 °C) or to excessively hot surfaces, such as heated floors in operation or surfaces exposed to direct sunlight. Do not apply with a brush or roller and do not use the product outdoors.

PRECAUTIONS:

- Do not apply LIGNOLIFE® with a brush or roller. For indoor use only.
- Do not apply LIGNOLIFE® to cold surfaces (below 7 °C).
- Avoid cleaning surfaces treated with LIGNOLIFE® using strongly alkaline or acidic cleaners (such as ammonia, sodium hypochlorite or acidic cleaners) or solvent-based products (such as ethyl alcohol).
- Do not apply the product to excessively hot surfaces, such as heated floors in operation or surfaces exposed to direct sunlight.

NOTES:

Our recommendations are based on current research knowledge and are intended to give the best information to the buyer-user. However, these indications require preliminary examinations and tests to the fields of use, to the types of materials present and to the various conditions of application. The user decides independently on suitability and on the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products.
Rev3-Ver300322

WARNINGS:

Hazard statements: Safety data sheet available on request.

Contains: Rosin acids, fumarated, esters with pentaerythritol. May produce an allergic reaction.

VOC (Directive 2004/42/EC): One-pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition: 19,00. – Limit value: 140,00

Rev3-Ver300322

PACKAGING:

- 1 L PE bottle – boxes of 6.
- 5 L PE container – boxes of 4.

YIELD:

The coverage of LIGNOLIFE® may vary depending on:

- the absorbency of the surface;
- the application method;
- the thickness of the applied coat;
- the number of coats applied.

Approximate coverage

1 L = 30–40 m² per coat

Actual coverage may vary depending on the absorbency of the substrate, the amount of product applied and the application method.

TECHNICAL DATA:

- Physical state: white liquid
- Specific weight (g / cm³): 1.025
- pH: 8
- Flashpoint (ASTM): not flammable
- Solubility in water: miscible in water
- Drying time: 2 – 3 hours
- Consolidation time: 24 hours
- Odour: characteristic

STORAGE:

Keep the product tightly closed at temperatures between 0°C and + 30°C and not exposed to sunlight for a long time. The stored product has a useful life of 2 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it