



BIOTOP OPACO

MATT FINISHING WAX FOR WOOD IMPREGNATED WITH OIL AND/OR WAX



User guide

DESCRIPTION:

O/A emulsion based on vegetable waxes, paraffin wax, fatty acid ester, resin, non-ionic surfactants.

FIELDS OF APPLICATION:

On all types of wooden surfaces inside (parquet, planks, furniture, tables, beams and wooden structures in general).

CHARACTERISTICS:

BIOTOP OPACO is a specific finisher for oil-impregnated wood surfaces placed inside: parquet, planks, furniture, tables, beams, and wooden structures in general.

BIOTOP OPACO:

- is a water-based product, not dangerous and easy to use;
- is strongly recommended at the end of the treatments with oily-waxy impregnations, as it protects the oil-impregnated wooden surfaces from wear over time and prevents the reapplication of the impregnation;
- leaves a matte appearance to the surface without altering the material, does not form a thick film on the surface leaves a good vapor permeability to the material;
- makes a micro-waxy resin layer on the material, easy to apply, which reduces dirt penetration and makes the surfaces easier and faster to clean;
- is preserved over time through ordinary cleaning with the detergent PULIBRILL and the maintenance wax anti-dirt, anti-degradation BIOCARE OPACO.

INSTRUCTIONS FOR USE:

- Apply on clean and dry surfaces;
- Shake very well before use;
- Apply the product in small quantities of product on the surface and distribute with a soft cloth, spreading fleece evenly on the surface;
- Do not step on the product during drying.

Generally dry in 1-2 hours.

PRECAUTIONS:

- does not apply to painted floors;
- roller and brush are not recommended.

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products.

Rev3-Ver150322

WARNINGS:

WARNINGS : NONE

Hazard statements: Safety data sheet available on request.

Rev3-Ver150322

PACKAGING:

- 1 lt Plastic bottle – box 6 pcs;
- 5 lt Plastic jerrycan – box 4 pcs.

YIELD:

- Approximately 1lt/ 30 – 40 sqm.

TECHNICAL DATA:

- Physical state: white liquid
- Specific gravity (g/cm3): 1
- pH: 8
- Flame point (ASTM): > 90 °C
- Solubility in water: miscible in water
- Drying time: 30 – 60 minutes
- Consolidation time: 24 hours

STORAGE:

Keep the product tightly closed at temperatures between 0 °C and +30 °C and not exposed to sunlight for a long time. The stored product has a useful life of 2 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it