



LIGNOLIFE OPACO

RESTORATION FINISHER FOR OPAQUE VARNISHED PARQUET



User guide

DESCRIPTION:

Emulsion based on carnauba wax and resins.

FIELDS OF APPLICATION:

On all opaque varnished wooden surfaces (parquet, coatings, furniture, interior doors, and windows).

CHARACTERISTICS:

LIGNOLIFE OPACO is a carnauba-based resin-waxy finisher, specific for restoring parquet or opaque varnished wood.

LIGNOLIFE OPACO:

- is an easy-to-use, odorless, water-based product;
- can be applied to all internal opaque varnished wood surfaces (parquet, coatings, furniture, doors), where the paint has lost tone;
- gives a new tone to the material and a natural opaque finish;
- gives new protection to the paint, and is resistant to wear from foot traffic, dirt, water, and detergents;
- is a self-levelling product;
- is easy to maintain over time with ordinary cleaning with the PULIBRILL detergent and with the application of BEAUTY FLOOR OPACO maintenance wax once every 6-12 months.

On wooden surfaces, LIGNOLIFE OPACO cannot replace repainting in the points where the paint has been completely removed by wear (eg gray stains and places where the wood is simply wet with water).

INSTRUCTIONS FOR USE:

Before applying LIGNOLIFE OPACO, perform an extraordinary cleaning with PULIBRILL and WHITE BUFFER, in order to degrease the surface.

- Shake well before use;
- Apply 2 coats of LIGNOLIFE OPACO. The product is distributed with a fleece spreader, microfibre cloth, or sponge. It should be applied in a thin layer, wetting the surface evenly and without leaving excesses;
- Apply the second coat as soon as the first is dry;
- It dries quickly, usually in 2 – 3 hours in well-ventilated areas.

PRECAUTIONS:

- avoid application by brush or roller. Do not use outdoors;
- avoid applying LIGNOLIFE on surfaces that are too cold ($<7^{\circ}\text{C}$);
- avoid using strong alkaline and acid detergents (eg ammonia, sodium hypochlorite, various acids) and solvents (eg ethyl alcohol) when cleaning surfaces treated with LIGNOLIFE OPACO;
- avoid applying the product on surfaces that are too hot (eg radiant floors or floors exposed directly to the sun's rays).

NOTES:

Our recommendations are based on current research knowledge and are intended to give the best information to the buyer-user. However, these indications require preliminary examinations and tests to the fields of use, to the types of materials present and to the various conditions of application. The user decides independently on suitability and on the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. Rev1-Ver300322

WARNINGS:

Hazard statements: Safety data sheet available on request.

Contains: Rosin acids, fumarated, esters with pentaerythritol. May produce an allergic reaction.

VOC (Directive 2004/42/EC): One-pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition: 19,00. – Limit value: 140,00

Rev1-Ver300322

PACKAGING:

- 1 lt Plastic bottle – 6 pcs box;
- 5 lt Plastic tank – 4 pcs box.

YIELD:

- 1 lt / 30-40 m² (for single passage).

TECHNICAL DATA:

- Physical state: white liquid
- Specific weight (g / cm³): 1.025
- pH: 8
- Flashpoint (ASTM): not flammable
- Solubility in water: miscible in water
- Drying time: 2 – 3 hours
- Consolidation time: 24 hours

STORAGE:

Keep the product tightly closed at temperatures between 0°C and + 30°C and not exposed to sunlight for a long time. The stored product has a useful life of 2 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it