



OX FIVE PLUS

STRONG AGING PRIMER FOR WOOD



User guide

DESCRIPTION:

Strong alkaline solution for the aging of wood essences and white inorganic pigments.

FIELDS OF APPLICATION:

For the ageing treatment of larch, elm, oak and chestnut raw and untreated.

CHARACTERISTICS:

OX FIVE PLUS is a strong alkaline solution specific for the aging of raw and untreated oak, chestnut, larch and elm.

OX FIVE PLUS:

- ages the wooden surface darkening it, without causing strong and uneven darkening of the wood essences;
- can be easily applied on both vertical and horizontal surfaces;
- leaves no residue on the wood surface;
- allows the subsequent application of any finish (painting – waxing – impregnation).

INSTRUCTIONS FOR USE:

- Distribute OX FIVE PLUS on the surface with a brush or a wax spreader, homogeneously, following the absorption of the wood;
- The aging action is progressive until the material is dry;
- The effect is in function of the cycles of application performed (max 2 hands);
- The possible 2 hand is done as soon as the surface is dry (2 – 4 hours);
- Remove the wood brittle after application of OX-FIVE PLUS, using not too fine-grained abrasive paper or net (e.g. 100).

PRECAUTIONS:

- avoid contact with aluminium surfaces;
- wear gloves and goggles.

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products.
Rev5-Ver140222

WARNINGS:



WARNING: DANGER

Hazard statements: Causes severe skin burns and eye damage.

Precautionary statements: Wear protective gloves / clothing and eye / face protection. – Do not breathe dust/fume/gas/mist/vapours/spray. – IF SWALLOWED: rinse mouth. Do NOT induce vomiting. – IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower. – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. - Immediately call a POISON CENTER / doctor.

Contains: sodium hydroxide.

UFI: 8X20-40YK-G00D-5RMV

FOR PROFESSIONAL USE

Rev5-Ver140222

PACKAGING:

- 1 lt Pe bottle – box 6 pieces;
- 5 lt Pe tank – box 4 pieces.

YIELD:

- Depending on the absorption of wood 1 lt / 6 – 12 m².

TECHNICAL DATA:

- Physical state: liquid
- Color: opalescent white
- Specific gravity (g/cm³): 1,07
- pH (20 ?? C) of the pure product: 14
- Flame point (ASTM): > 90 °C
- Solubility in water: soluble in water

STORAGE:

Keep the product tightly closed and at a temperature between 5 and 30 °C in an aerated environment, away from heat sources and not exposed to sunlight for a long time. When stored at low temperatures (<10 °F) the product can become dense, but without affecting its use or performance. The stored product has a useful life of 5 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it