



FONDO COLARIN2

BLACK PRIMER FOR INDOOR WOOD



User guide

DESCRIPTION:

Black dye solution in water.

FIELDS OF APPLICATION:

To carry out a gray background treatment on all types of wooden surfaces placed inside.

CHARACTERISTICS:

FONDO COLARIN2 is a product for carrying out a gray background treatment on all types of wooden surfaces placed inside.

FONDO COLARIN2:

- is a black pigmented base in water dispersion for all types of raw wood indoors;
- is a product of easy application on wood;
- can be diluted in water to have more or less gray customized effects;
- it is easy to sand;
- can be painted or oiled;
- is a product without VOC emissions.

INSTRUCTIONS FOR USE:

Shake well before use and ensure complete pigment dispersion.

You can apply pure or diluted in water depending on the gray effect of the desired background:

- pure for dark gray effects;
- diluted 1 part product in 1/3 part water for intermediate grey effects;
- diluted 1 part in 4/10 parts water for light gray effects.

How it applies:

- It can be applied to sponge, rag or brush by wetting evenly the surface to be treated until it is completely saturated;
- Normally dries in 30-60 minutes depending on the ventilation;
- During the wet and cold season and in closed or poorly ventilated rooms, the drying time can lengthen considerably;
- After drying, the base can be sanded to the desired effect and the wood can be immediately painted or oiled;

To obtain "graying" effects of the wood, it is advisable to apply white pigmented impregnating agents (e.g. TIROIL, OLIO TECNO mixed with 2-10% OILTONER BIANCO or HYDROIL INTERNO mixed with 2-10% IDROTONER BIANCO).

PRECAUTIONS:

None.

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products.

Rev2-Ver231120

WARNINGS:

PACKAGING:

- 1 lt Plastic bottle;
- 5 lt Plastic tank.

YIELD:

- Approximately 1lt/ 6 – 8 m².

TECHNICAL DATA:

- Physical state: black liquid
- Specific gravity (g/cm³): 1
- pH: 7
- Flame point (ASTM): non-flammable.
- Solubility in water: soluble in water.
- Drying time: 30-60 minutes (in ventilated environments).

STORAGE:

Keep the product tightly closed at temperatures between 0 °C and +30 °C and not exposed to sunlight for a long time. The stored product has a useful life of 2 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it