



FUGA PROTETTA

STAIN-RESISTANT AND DIRT-REPELLENT TREATMENT FOR CEMENTITIOUS AND SYNTHETIC GROUT LINES



User guide

DESCRIPTION:

FUGA PROTETTA is a water-based stain-resistant and dirt-repellent protective treatment formulated to reduce the absorption of dirt, liquids and greasy substances in cementitious and synthetic grout lines. It is designed to protect grout lines on floors and wall coverings, both indoors and outdoors, without altering the original appearance of the surface.

FIELDS OF APPLICATION:

Recommended for stain-resistant and dirt-repellent protection of:

- cementitious grout lines on indoor floors
- grout lines in bathroom and kitchen wall coverings
- outdoor grout lines on floors and terraces
- synthetic grout lines
- surfaces exposed to dirt and liquid absorption

CHARACTERISTICS:

FUGA PROTETTA is a stain-resistant and dirt-repellent protective treatment specifically designed for grout lines on floors and wall coverings. In particular:

- it significantly reduces the absorption of liquids and greasy substances in cementitious and synthetic grout lines;
- it can be applied on both indoor and outdoor surfaces;
- it does not create surface films, remains invisible and does not alter the original appearance or colour tone of the material;
- outdoors, it helps keep grout lines cleaner thanks to its stain-resistant protection against weather exposure and foot traffic;
- it is a water-based, odourless product, not classified as hazardous and easy to apply;
- it can be easily reapplied whenever needed to maintain long-lasting protection.

INSTRUCTIONS FOR USE:

Ready-to-use product. Apply only on perfectly clean and dry surfaces.

Pre-cleaning with PULI FUGHE is recommended.

- Shake the product well to evenly distribute the protective components in the formulation.
- Spray small amounts of product directly onto the grout lines to be treated.
- Spread evenly with a soft cloth, avoiding surface buildup or excess product.
- Allow the surface to dry: the treatment dries in approximately 10–15 minutes and becomes walkable.
- Wait about 12 hours for the product to achieve maximum stain-resistant protection.
- Avoid contact with water during the drying and curing phase of the treatment.

PRECAUTIONS:

The product is not suitable for:

- waterproofing surfaces exposed to continuous standing water above 10 cm, such as swimming pools or tanks;
- blocking rising damp coming from wet substrates;
- application on wet or not perfectly dry surfaces.

After application, protect treated surfaces from rain or water exposure for at least 8 hours.

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the

WARNINGS:

The product is not classified as hazardous according to Regulation (EC) No. 1272/2008 (CLP) and subsequent amendments and adaptations.

VOC (Directive 2004/42/EC): Primer.
VOC expressed in g/litre of product ready for use: 0,00.
Maximum limit: 30,00

Rev1-Ver300124

PACKAGING:

- 750 ml PE spray bottle – boxes of 6 units

YIELD:

Product coverage depends on grout porosity, the quantity applied and the absorption level of the treated surface.

With one 750 ml bottle, the approximate coverage is:

- Protection of compact or low-porosity grout lines
On indoor surfaces in good condition with regular grout lines, one bottle covers approximately 45–50 m².
- Protection of medium-absorption grout lines
On more porous grout lines or surfaces exposed to frequent dirt buildup, 750 ml covers approximately 35–45 m².
- Highly porous or worn grout lines
On very absorbent or deteriorated surfaces, a larger amount of product may be required, with an approximate coverage of 30–35 m².
- Outdoor applications
On outdoor floors and wall coverings, coverage may vary depending on weather exposure, grout width and the absorption capacity of the material.

Correct and even application helps maintain long-lasting stain-resistant protection and makes routine surface cleaning easier.

TECHNICAL DATA:

- Physical state: opalescent liquid.
- Specific gravity (g/cm³):1,006.
- pH: 6-7.
- Flame point (ASTM): non-flammable.
- Solubility in water: miscible in water.
- Drying time: 8-12 hours (in ventilated rooms)
- Consolidation time: 48 hours.
- Odour: odourless

STORAGE:

Keep the product tightly closed and at a temperature between 5 and 30 °C in an aerated environment, away from heat sources and not exposed to sunlight for a long time. When stored at low temperatures (<10 °F) the product can become dense, but without affecting its use or performance. The stored product has a useful life of 5 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it