



# IDROFIN MATT

ANTI-DIRT, ANTI-WEAR MATT FINISHING WAX FOR STONE MATERIALS



## User guide

### DESCRIPTION:

O / A emulsion based on mineral waxes and acrylic-styrol emulsions.

### FIELDS OF APPLICATION:

For the final matte finish of treatments on absorbent stone materials placed inside: cotto, brick, highly absorbent natural stone, cement, mineral plaster.

### CHARACTERISTICS:

**IDROFIN MATT** is an opaque finish for absorbent stone materials placed inside: cotto, absorbent natural stone, terrazzo.

#### **IDROFIN MATT:**

- is a water-based, non-hazardous and easy-to-use product;
- is strongly recommended at the end of treatments with water-oil-repellent protective agents, oil-waxy impregnating agents, and leveling primers, as it protects the surfaces from wear over time and avoids the deterioration of the base treatment;
- does not alter the appearance of the material and does not form a thick film on the surface leaving a good vapor permeability to the material;
- creates an easy-to-apply resin-waxy micro-layer on the material, which reduces the penetration of dirt and makes surfaces easier and faster to clean;
- is preserved over time through ordinary cleaning with the FLORA detergent and the anti-dirt, anti-degradation maintenance wax REFIX LUCIDO.

### INSTRUCTIONS FOR USE:

Normally it is used pure.

- Apply on clean and dry surfaces;
- Shake well before use;
- Apply the product in small quantities of product on the surface and distribute with a soft cloth, fleece spreader evenly on the surface;
- Do not step on the product during drying;
- Apply any second coat as soon as the first is dry.

It generally dries in 2-3 hours.

Application types:

- 1 coat: on smooth and not very absorbent surfaces;
- 2 coats: on rough surfaces.

### PRECAUTIONS:

- avoid application by brush or roller. Do not use outside;
- avoid applying IDROFIN on surfaces that are too cold ( $<5^{\circ}\text{C}$ );
- avoid using strong alkaline and acid detergents (eg ammonia, sodium hypochlorite, various acids) and solvents (eg ethyl alcohol) when cleaning surfaces treated with IDROFIN.

### NOTES:

Our recommendations are based on current research knowledge and are intended to give the best information to the buyer-user. However, these indications require preliminary examinations and tests to the fields of use, to the types of materials present and to the various conditions of application. The user decides independently on suitability and on the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products.  
Rev4-Ver280322

## WARNINGS:

**Hazard statements:** safety data sheet available on request.

VOC (Directive 2004/42/EC): One-component high-performance paints.  
VOC expressed in g/liter of ready-to-use product: 22,00. – Maximum limit: 140,00

Rev4-Ver280322

## PACKAGING:

- 1 lt Plastic bottle 6 pcs box;
- 5 lt Plastic tank 4 pcs box;
- 20 l plastic tank.

## YIELD:

Depending on the absorption of the materials.  
– on materials with rough surfaces 1 lt / 10-18 m<sup>2</sup>;  
– on materials with smooth surfaces 1 lt / 20-30 m<sup>2</sup>.

## TECHNICAL DATA:

Physical state: white liquid  
Specific weight (g/cm<sup>3</sup>): 1  
pH: 8  
Flashpoint (ASTM): not flammable  
Solubility in water: miscible in water  
Drying time: 2 – 3 hours  
Consolidation time: 24 hours

## STORAGE:

Keep the product tightly closed at temperatures between 0°C and + 30°C and not exposed to sunlight for a long time. The stored product has a useful life of 2 years.

MARBEC SRL

Via Croce Rossa 51  
51037 - Montale PT  
Italia

CUSTOMER SERVICE

Tel +39 0573959848  
Whatsapp +39 3348578502  
Email [contatti@marbec.it](mailto:contatti@marbec.it)