



# REFIX LUCIDO

## MAINTENANCE WAX FOR COTTO AND STONE



### User guide

#### DESCRIPTION:

O/A emulsion based on vegetable waxes, mineral waxes and resins.

#### FIELDS OF APPLICATION:

Maintainer of all stone surfaces treated with emulsions like IDROFIN.

#### CHARACTERISTICS:

**REFIX LUCIDO** is a glossy maintenance wax for treated absorbent stone materials as cotto, stone and cement terrazzo placed inside.

#### REFIX LUCIDO:

- is a water based product, not dangerous and easy to use;
- preserves and protects over time the protective and aesthetic characteristics of the initial glossy finish;
- makes the surfaces easier to clean and maintain;
- renews the surface protection of the treatment;
- does not form films or glossy films;
- leaves a pleasant smell in the environment;
- it can be dry polished to increase and maintain gloss.

#### INSTRUCTIONS FOR USE:

- Apply on clean and dry surfaces;
- Shake before use;
- Apply the product in small quantities of product on the surface and distribute with a soft cloth, spreading fleece and evenly on the surface;
- Do not step on the product during drying;
- To increase the gloss after drying or to remove tread marks, rub the surface treated with a wool cloth, polisher with felt, red pads, single brush with red discs.

It generally dries in 1-2 hours.

#### Periodicity of use:

- every 4-6 months: on heavily trampled and heavily worn surfaces (e.g. shops, public places, bars, restaurants, kitchens, entrances, bathrooms, etc.);
- every 12 months: on poorly trampled surfaces (e.g. sleeping areas, salt, etc.).

#### PRECAUTIONS:

- avoid the use of strongly alkaline detergents, ammoniacal detergents and solvents in the cleaning of the surfaces maintained with REFIX LUCIDO.

#### NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products.  
Rev4-Ver060422

#### WARNINGS:

**Hazard statements:** safety data sheet available on request.

#### PACKAGING:

- 1 lt Plastic bottle – box 6 pcs;
- 5 lt Plastic jerrycan – box 4 pcs.

#### YIELD:

Depending on the surface finish of the material:

- approximately 1 lt /30 -40 m².

#### TECHNICAL DATA:

- Physical state: white liquid
- Specific gravity (g/cm3): 1,00
- pH: 8
- Flame point (ASTM): > 90°C
- Solubility in water: soluble in water
- Drying time: 30 – 60 minutes
- Consolidation time: 2 hours

#### STORAGE:

Keep the product tightly closed at temperatures between 0 °C and +30 °C and not exposed to sunlight for a long time.

STORAGE PERIOD: The product thus preserved has a useful life of 2 years.

MARBEC SRL

Via Croce Rossa 51  
51037 - Montale PT  
Italia

CUSTOMER SERVICE

Tel +39 0573959848  
Whatsapp +39 3348578502  
Email [contatti@marbec.it](mailto:contatti@marbec.it)