



DILUOIL

THINNER FOR OIL-WAXY IMPREGNATING PRODUCTS



User guide

DESCRIPTION:

Mixture of denatured aliphatic hydrocarbon solvents.

FIELDS OF APPLICATION:

Solvent for the dilution of oil-waxy impregnating products and the facilitation of their absorption in low-porous materials.

CHARACTERISTICS:

DILUOIL is a solvent-based diluent of oil-waxy impregnating products to facilitate their absorption in non-porous materials.

DILUOIL:

- can also be used in the cleaning of all wood surfaces soiled with greasy substances or soot and for the surface de-resination of resinous wood species;
- is indicated as a thinner of oil-waxy impregnating products such as TIROIL, OLIO TECNO, FLUOIL, OLIO 41, TUSCANIA OIL, WET OUT, OIL WET;
- is indicated for the extraordinary maintenance and recovery of floors treated with deteriorated oil-waxy impregnations;
- is a mixture of solvents of low danger to man and the environment;
- leaves no halos and does not stain the wood essence.

INSTRUCTIONS FOR USE:

As a thinner it can be used in all concentrations.

PRECAUTIONS:

- protect all painted surfaces from contact with DILUOIL;
- the product, in particular on decorated wooden structures, may have an undesirable solvent action on the colours of the decoration. Therefore, in these cases, it is advisable to make small preliminary tests.

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products.

Rev5-Ver230222

WARNINGS:



WARNING: DANGER

Hazard statements: Flammable liquid and vapour. – May be fatal if swallowed and enters airways. – May cause drowsiness or dizziness. – Repeated exposure may cause skin dryness or cracking.

Precautionary statements: – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. – Do NOT induce vomiting. – Wear protective gloves/ protective clothing / eye protection / face protection. – Avoid breathing dust / fume / gas / mist / vapours / spray. – IF SWALLOWED: Immediately call a POISON CENTER / doctor / . . . – IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics "

UFI:2940-800X-D00A-R6XW

Rev5-Ver230222

PACKAGING:

- 1 lt conf. can – box 6 pcs;
- 5 lt conf. can – box 4 pcs.

YIELD:

- Depending on the consistency of the dirt to be removed or the degree of dilution desired.

TECHNICAL DATA:

- Physical state: clear colourless liquid
- Specific gravity (g/cm³) at 20°C: 0.771
- pH: n.a.
- Flame point (ASTM): 40°C
- Solubility in water: not soluble

STORAGE:

Keep the product tightly closed and at a temperature between 5 and 30 °C in an aerated environment, away from heat sources and not exposed to sunlight for a long time. When stored at low temperatures (<10 °F) the product can become dense, but without affecting its use or performance. The stored product has a useful life of 5 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it