

# **OX FIVE**

# AGING PRIMER FOR WOOD



# User guide

#### **DESCRIPTION:**

Aqueous solution of non-corrosive inorganic salts.

#### FIELDS OF APPLICATION:

Soluzione liquida non pericolosa per l'invecchiamento delle superfici in rovere e castagno.

#### **CHARACTERISTICS:**

Characteristics and use:

OX FIVE is a non-hazardous liquid solution for ageing tannin-rich oak and chestnut surfaces.

#### **OX FIVE:**

- ages the wooden surface without causing strong and uneven darkening of the wood species;
- · can be easily applied on both vertical and horizontal surfaces;
- is a non-hazardous product that is safe to use in all building site situations;
- leaves no residue on the wooden surface;
- allows the subsequent application of any finish (painting waxing impregnation).

## **INSTRUCTIONS FOR USE:**

- Distribute OX FIVE on the surface with a brush or spreader fleece, evenly, following the absorption of the wood;
- The ageing action is progressive until the material is dry;
- The effect depends on the application cycles carried out (max. 2 coats);
- The 2nd coat is applied as soon as the surface is dry (2 4 hours);
- Eliminate the defibration of the wood that forms after the application of OX-FIVE, using a not too fine grit paper or abrasive net (e.g. 100).

The intensity and final result of ageing depends on the type of wood species and may vary, for the same wood, from element to element (planks, boards, beams, etc.). It is therefore advisable to take sufficiently representative samples of the finished product.

#### PRECAUTIONS:

· None.

# NOTES:

Our indications are based on current research knowledge and are intended to give the best guidance to the buyer-user. However, such indications require examination and testing prior to the areas of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and field of use. MARBEC Srl accepts no liability for the incorrect use of its products. Rev5-Ver140222

#### **WARNINGS:**



WARNINGS: DANGER

Indications of danger: Causes serious eye damage.

Precautionary statements: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. – Protect eyes/face. – Immediately call a POISON CENTRE / doctor/

. . .

Contains: ammonium carbamate.

UFI: 8P20-M0WD-J00W-5QVP

Rev5-Ver140222

#### **PACKAGING:**

- 1 It Plastic Bottle 6 Pieces box;
- 5 lt Plastic Tan 4 pieces box;

## YIELD:

• Depending on wood absorption capacity 1 litre/8-12 sqm each coat.

## **TECHNICAL DATA:**

- · Physical state: liquid
- · Colour: pink
- Specific weight (g/cm3): 1.05
- pH (20°C) of pure product: 10-11
- Flash point (ASTM): non-flammable
- Solubility in water: soluble in water

# STORAGE:

Store the product tightly closed at temperatures between 0°C and +30°C and not exposed to sunlight for long periods.

STORAGE PERIOD: The product has a shelf life of 5 years when stored as advised.

MARBEC SRL

**CUSTOMER SERVICE**