

LIGNOLUX

WAX FOR CLEANING AND MAINTENANCE OF PARQUET AND OILED AND/OR WAXED WOOD



User guide

DESCRIPTION:

Solution based on mineral waxes, vegetable waxes, odourless aliphatic solvent oils and D-limonene

FIELDS OF APPLICATION:

For the finishing, protection and maintenance of all types of wood surfaces treated with oil and/ or wax inside (parquet, coatings, furniture).

CHARACTERISTICS:

LIGNOLUX is a wax washer product for cleaning, protection and maintenance of internal wooden surfaces (floors, walls, windows, furniture) impregnated with oil and/or wax.

LIGNOLUX:

- is a very fine liquid solution of oils and waxes with great penetration and coverage of wood fibres;
- cleans, degreases and nourishes the material, leaving a satin waxy finish for the wood essence;
- has excellent resistance to trampling and dirt;
- restores, preserves and protects over time the protective and aesthetic characteristics of the initial treatment;
- It is easily re-usable and maintainable over time.

INSTRUCTIONS FOR USE:

- Apply small amounts of LIGNOLUX on the surface and distribute the product in a thin layer with soft cloth and leave no excess, until completely dry;
- As soon as the surface dry, you can polish it with polishing machine or brush / buffer / soft cloth;
- Only on very rough and extremely uneven wooden surfaces, the application of a second coat may be required.

For routine maintenance, you can polish the surface dry with the use of a polisher.

Periodicity of use:

- every 2-3 months: on surfaces intensely trampled and subject to heavy wear (e.g. shops, public places, bars, restaurants, kitchens, entrances, bathrooms, etc.);
- every 4-6 months: on poorly trampled surfaces (e.g. sleeping areas, salt, etc.).

PRECAUTIONS:

• do not use LIGNOLUX on painted wood.

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC SrI assumes no responsibility for the incorrect use of its products. Rev4-Ver240222

WARNINGS:









WARNING: DANGER

Hazard statements: Flammable liquid and vapour. – May be fatal if swallowed and enters airways. – May cause an allergic skin reaction. – May cause drowsiness or dizziness. – Toxic to aquatic life with long lasting effects. – Repeated exposure may cause skin dryness or cracking.

Precautionary statements: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. – Do NOT induce vomiting. – Wear protective gloves/ protective clothing / eye protection / face protection. – Avoid breathing dust / fume / gas / mist / vapours / spray. – IF SWALLOWED: Immediately call a POISON CENTER / doctor / . . . – IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, Hydrocarbons, C9, aromatics D-limonene

VOC (Directive 2004/42/CE): Impregnating agents for wood that form a film of minimum thickness. VOC given in g/litre of product in a ready-to-use condition: 640,00. – Limit value: 700,00

UFI:QH50-A0PG-P008-003T

Rev4-Ver240222

PACKAGING:

- 1 It conf. Can box 6 pieces;
- 5 lt conf. Can box 4 pieces.

YIELD:

Depending on wood absorption:

• approximately 1 lt / 30 - 40 m².

TECHNICAL DATA:

- Time of physical state: colourless liquid
- Specific gravity: 0.79
- pH: n.d.
- Flame point (ASTM): 23 ? T ? 60°C
- Solubility in water: not soluble in water
- Drying time: 30-60 minutes depending on ventilation
- Consolidation time: 1 day
- · Kinematic viscosity: not available
- Consolidation: 24 hours

STORAGE:

Keep the product tightly closed at temperatures between 0 °C and +30 °C and not exposed to sunlight for a long time. The stored product has a useful life of 2 years.

MARBEC SRL

CUSTOMER SERVICE