

# **BIOCARE**

# PROFESSIONAL WAX FOR WOOD AND PARQUET MAINTENANCE



# User guide

#### **DESCRIPTION:**

O/A emulsion of waxes, resins, non-ionic surfactants.

#### FIELDS OF APPLICATION:

Protective and maintenance wax for floors, walls, windows, furniture, and wooden surfaces generally impregnated with oil. For internal use.

#### **CHARACTERISTICS:**

BIOCARE is a maintenance and protection wax for internal use of floors, walls, windows, furniture, and wooden surfaces generally impregnated with oil.

#### **BIOCARE:**

- is a water-based product, not dangerous and easy to use;
- preserves and protects over time the protective and aesthetic characteristics of the initial finish;
- · makes the surfaces easier to clean and maintain;
- renews the surface protection of the treatment;
- does not form films or glossy films;
- · leaves a pleasant smell in the environment;
- is a self-relaxing wax. It can be dry-polished to increase and maintain gloss.

#### **INSTRUCTIONS FOR USE:**

- Apply on clean and dry surfaces;
- Shake before use:
- Apply the product in small quantities of product on the surface and distribute with a soft cloth, spreading fleece and evenly on the surface;
- Do not step on the product during drying;
- To increase the gloss after drying or to remove tread marks, rub the surface treated with a wool cloth, polisher with felt, blue bufffers, monobrush with blue discs.

Generally dry in 1-2 hours.

#### Periodicity of use:

- every 4-6 months: on surfaces intensely trampled and subject to heavy wear (e.g. shops, public places, bars, restaurants, kitchens, entrances, bathrooms, etc.);
- every 12 months: on poorly trampled surfaces (e.g. sleeping areas, salt, etc.).

## PRECAUTIONS:

- do not use BIOCARE on painted wood;
- avoid the use of highly alcoholic detergents when cleaning surfaces treated with BIOCARE.

#### NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present, and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC SrI assumes no responsibility for the incorrect use of its products. Rev3-Ver170322

#### **WARNINGS:**

WARNING: NONE

Hazard statements: Safety data sheet available on request.

Rev3-Ver170322

## **PACKAGING:**

- 1 It Plastic bottle box 6 pcs;
- 5 It Plastic tank box 4 pcs.

#### YIELD:

• Depending on the surface finish of the material 1 lt / 30 – 40 sqm.

# TECHNICAL DATA:

Physical state: pink liquidSpecific gravity (g/cm3): 1

• pH: 8

• Flame point (ASTM): non-flammable

Solubility in water: total
Drying time: 30 – 60 minutes
Consolidation time: 24 hours

## STORAGE:

Keep the product tightly closed at temperatures between 0  $^{\circ}$ C and +30  $^{\circ}$ C and not exposed to sunlight for a long time. The stored product has a useful life of 2 years.