

# **PULI FUGHE**

# WHITENING STAIN REMOVER FOR FLOOR JOINTS



## User guide

#### **DESCRIPTION:**

Liquid alkaline solution based on alkali, surfactants, phosphates, sequestrants and solvents.

#### FIELDS OF APPLICATION:

For deep and degreasing cleaning of cementitious or synthetic joints of ceramic floors and walls: porcelain tiles, single and double-fired tiles, porcelain, glass mosaics, klinker.

### **CHARACTERISTICS:**

PULI FUGHE is a detergent for the deep degreasing and whitening cleaning of cement or synthetic joints of ceramic floors and walls: porcelain tiles, single and double-fired, porcelain, glass mosaics, klinker.

#### **PULI FUGHE:**

- thoroughly cleans the joints of the floors and walls eliminating blackening due to dirt accumulated over time:
- effectively removes grease, stains left by food, inorganic dirt of trampling restoring the original appearance;
- does not damage ceramic tiles. It contains neither acids nor bleach.

Do not apply on cotto, wax-treated stones and cement, on wood, linoleum and synthetic materials.

# **INSTRUCTIONS FOR USE:**

- Spray on the surface to be cleaned/degreased;
- Wait a few minutes and in case of stubborn dirt increase the contact time of PULI FUGHE with the surface to be cleaned;
- Rub the surface with nylon brush;
- Then rinse with warm water.

### PRECAUTIONS:

- do not use on wood, absorbent materials treated with wax (e.g. cotto);
- protect painted and anodized aluminium surfaces from contact with PULI FUGHE;
- the product can dull the methacrylate: pay attention near the bathtubs made with this material.

## NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. Rev8-Ver130123

## WARNINGS:



WARNING: DANGER

Hazard statements: Causes severe skin burns and eye damage.

Precautionary statements: Do not breathe dust / fume / gas / mist / vapours / spray. – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. – IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. – Wear

protective gloves/ protective clothing / eye protection / face protection. – Immediately call a POISON CENTER / doctor / . . . – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Contains: POTASSIUM HYDROXIDE, ETHANOLAMINE

Ingredients in accordance with Regulation (EC) No 648/2004: Non-ionic surfactants <5%, anionic surfactants <5%, phosphates<5%

UFI: ADA0-6014-400F-QFAG

Rev10-Ver12022025

### **PACKAGING:**

- 750 ml PE spray bottle box 6 pcs;
- 5 It PE Tank box 4pcs.

## YIELD:

Depending on the size and number of joints per unit area:

• Average for 30X30 tiles: 1 lt / 40 - 50 m².

## TECHNICAL DATA:

- Physical state: colourless liquid
- Specific gravity (g/cm3): 1,06
- pH (20 °C) of the pure product: 12
- Flame point (ASTM): non-flammable
- · Solubility in water: soluble in water

## STORAGE:

Keep the product tightly closed at temperatures between 0  $^{\circ}$ C and +30  $^{\circ}$ C and not exposed to sunlight for a long time. The stored product has a useful life of 2 years.

MARBEC SRL

**CUSTOMER SERVICE**