



ANTISPORCO

STAIN RESISTANT PRODUCT FOR PORCELAIN TILES



User guide

DESCRIPTION:

Water-based micro-emulsion of anti-dirt protectors.

FIELDS OF APPLICATION:

Invisible anti-dirt stain protection specific for porcelain tiles floors and walls. It drastically reduces the absorption of dirt, facilitating and speeding up ordinary cleaning.

CHARACTERISTICS:

ANTISPORCO is an anti-stain protective product specific for matt, glossy or lapped porcelain tiles floors and walls.

ANTISPORCO:

- forms an invisible anti-stain chemical barrier on the surface, which does not create films and does not alter the appearance and the color tone of the material;
- is a water-based product, odorless, non-dangerous, and easy to use;
- protects porcelain tiles and joints from daily dirt;
- reduces the absorption of the material, facilitates and speeds up ordinary cleaning;
- reduces the use of detergents;
- if applied before the filling of the porcelain tiles floors, avoids that the filler settles in the microporosities of the material, making easier the post-construction cleaning;
- has a duration of 6/12 months depending on foot traffic and washing and can be easily reapplied.

INSTRUCTIONS FOR USE:

- Shake well before use;
- Apply ANTISPORCO only on perfectly clean and dry surfaces;
- Spray small quantities of product on the surface and distribute evenly with a soft cloth;
- The surface dries in about 10/15 minutes and can be walked on;
- Achieves the maximum stain protection after approximately 12 hours. During this time, avoid washing the surface with water;
- Any excess product after drying must be removed by wiping with a damp cloth of ANTISPORCO on the surface.

It is recommended to apply ANTISPORCO after the extraordinary stain remover cleaning carried out with POWER DET or the periodic extraordinary cleaning with GRES LINDO, in order to thoroughly clean the porcelain tiles before application.

PRECAUTIONS:

- None.

NOTES:

Our recommendations are based on current research knowledge and are intended to give the best information to the buyer-user. However, these indications require preliminary examinations and tests to the fields of use, to the types of materials present and to the various conditions of application. The user decides independently on suitability and on the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. Rev4-Ver150322

WARNINGS:

Hazard statements: safety data sheet available on request.

Rev4-Ver150322

PACKAGING:

- 0,75 lt PE spray – 6 pcs box;
- 5 lt Plastic tank – 4 pcs box.

YIELD:

- Aproximately 1 lt /40-60 m².

TECHNICAL DATA:

- Physical state: opalescent liquid
- Specific weight (g / cm³): 1
- pH: 6-7
- Flashpoint (ASTM): not flammable
- Solubility in water: miscible
- Drying time: 15-30 min
- Consolidation time: 8-12 hours

STORAGE:

Keep the product tightly closed at temperatures between 0 ° C and + 30 ° C and not exposed to sunlight for a long time. The stored product has a useful life of 2 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it