



OLIO RAVVIVANTE

REGENERATING IMPREGNATOR FOR VARNISHED WOOD

User guide

DESCRIPTION:

Oleo-waxy dispersion in aliphatic paraffinic solvent based on siccativ oils, mineral waxes, modified waxes, resins, lead-free dry metal salts.

FIELDS OF APPLICATION:

On all fixtures, floors, painted wooden structures placed outside and inside. Also ideal for regenerating old discolored paints on metal structures (e.g. painted aluminium).

CHARACTERISTICS:

OLIO RAVVIVANTE is a regenerating protective impregnation for doors, windows, shutters, shutters, varnished wooden floors.

OLIO RAVVIVANTE:

- is a hydro-oleophobic oil-waxy impregnation specific for the renewal of the wood surfaces painted inside and outside;
- restores the paint layer deteriorated by weathering, wear, matting and whitening,
- protects and revives the color of the material, without forming surface films;
- does not browse or create peelings.

INSTRUCTIONS FOR USE:

Apply on previously clean and dry surfaces. It is advisable to carry out a first extraordinary cleaning with SMACCHIO LEGNO and BLUE BUFFER and a second extraordinary cleaning with PULIBRILL or DETERCLEAN and BLUE BUFFER in order to remove stains and degrease the wood, to prepare it for the recovery phase.

- Shake OLIO RAVVIVANTE before use;
Distribute OLIO RAVVIVANTE in small quantities with a brush or cloth wetting and rubbing with a soft cloth all over the surface and following the absorption of wood and painting. The surface should appear homogeneous and slightly moist.

Dries normally in 12-24 hours.

PRECAUTIONS:

WARNING: do not accumulate rags, sponges, sawdust etc. soaked in OLIO RAVVIVANTE for the danger of spontaneous combustion! Dispose of them by wetting them well with water.

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products.
Rev7-Ver230222

WARNINGS:



WARNING: DANGER

Hazard statements: Flammable liquid and vapour. – May be fatal if swallowed and enters airways. – May cause



drowsiness or dizziness. – Harmful to aquatic life with long lasting effects. – Repeated exposure may cause skin dryness or cracking. – Contains: Cobalt bis (2-ethylhexanoate). May produce an allergic reaction.

Precautionary statements: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. – Do NOT induce vomiting. – Wear protective gloves/ protective clothing / eye protection / face protection. – Avoid breathing dust / fume / gas / mist / vapours / spray. – Call a POISON CENTRE / doctor / . . . if you feel unwell. – Store in a well-ventilated place. Keep container tightly closed. – Avoid release to the environment.

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic < 2% aromatic. Hydrocarbons, C9, aromatic.

VOC (Directive 2004/42/CE):
Impregnating agents for wood that form a film of minimum thickness.

VOC expressed in g/litre of product ready for use: 408,00. – Maximum limit: 700,00

UFI: 1V30-Q0JX-U00U-EH1K

Rev7-Ver230222

PACKAGING:

- 1 lt conf. Can – box 6 pcs.

YIELD:

- approximately 1lt / 70-100 m².

TECHNICAL DATA:

- Physical state: yellowish liquid
- Specific gravity (g/cm3) at 20 °C: 0,85
- pH: n.d.
- Flame point (ASTM): 23 ? T ? 60 ° C
- Solubility in water: not soluble
- Drying time: 12 – 24 hours depending on ventilation and temperature
- Consolidation time: 3 days

STORAGE:

Keep the product tightly closed and at a temperature between 5 and 30 °C in an aerated environment and away from heat sources and not exposed to sunlight for a long time. When stored at low temperatures (<10 °F) the product can become dense, but without affecting its use or performance. The stored product has a useful life of 5 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it