



BEAUTY FLOOR OPACO

MAINTENANCE WAX FOR MATT PAINTED WOOD



User guide

DESCRIPTION:

O/W emulsion of waxes, resins, and non-ionic surfactants.

FIELDS OF APPLICATION:

Maintainer of all matt-painted wooden surfaces.

CHARACTERISTICS:

BEAUTY FLOOR OPACO is a specific protection and maintenance wax for matt-painted wooden floors and surfaces. For internal use.

BEAUTY FLOOR OPACO:

- is a water-based product, not dangerous and easy to use;
- creates a waxy microfilm that protects matt-painted wooden surfaces from wear of detergents and trampling;
- retains the protective and aesthetic characteristics of the initial finish over time;
- makes surfaces easier to clean and maintain;
- leaves a pleasant smell in the environment.

INSTRUCTIONS FOR USE:

- Shake before use.
- Apply the product in small quantities to a soft cloth and spread a thin, even layer over the surface.
- Do not step on the product while drying.

It usually dries in 1-2 hours.

Frequency of use:

- every 2-3 months: on surfaces heavily trampled on and subject to heavy wear (e.g. shops, public places, bars, restaurants, kitchens, entrances, bathrooms, etc.);
- every 6-12 months: on surfaces that are rarely trampled (e.g. sleeping areas, halls, etc.).

PRECAUTIONS:

- avoid excesses of product so as not to have halos or opacities on the painted surfaces.

NOTES:

Our indications are based on current research knowledge and are intended to give the best indications to the buyer-user. However, these indications require preliminary examinations and tests for the fields of use, the types of materials present, and the various application conditions. The user decides independently on the suitability and field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. Rev2-Ver150322

WARNINGS:

WARNINGS: NONE

Hazard statements: Safety data sheet available on request. – Contains: Rosin acids, fumarates, esters with pentaerythritol
May produce an allergic reaction.

Rev2-Ver150322

PACKAGING:

- 1 lt pack. Can – box of 6 pieces;

- 5 lt pack. Can – box of 4 pieces.

YIELD:

- Depending on the surface finish of the material 1 liter / 50 – 80 m².

TECHNICAL DATA:

- Physical state: white liquid
- Specific weight (g/cm³): 1
- pH: 8
- Flashpoint (ASTM): non-flammable
- Solubility in water: miscible in water
- Drying time: 15 – 30 minutes
- Consolidation time: 2 hours

STORAGE:

Keep the product tightly closed at temperatures between 0°C and +30°C and not exposed to sunlight for a long time.

STORAGE PERIOD: The product stored in this way has a useful life of 5 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it