



PULIGRAFF LIQUIDO

PAINT REMOVER FOR REMOVING GRAFFITI FROM SURFACES, FACADES AND COATINGS



User guide

DESCRIPTION:

Thickened mixture of organic solvents.

FIELDS OF APPLICATION:

For removing graffiti on floors, facades, coatings and surfaces in general.

CHARACTERISTICS:

PULIGRAFF LIQUIDO is a solvent stain remover specific for removing graffiti on facades and coatings.

PULIGRAFF LIQUIDO:

- is a specific stain remover to quickly remove from surfaces the residues of graffiti, lacquers, synthetic enamels and paints in general;
- is neither alkaline nor acid, therefore it can be used safely even in the presence of metal surfaces and delicate stones;
- can be applied on all stone materials such as cotto, stone, glazed ceramics, klinker, porcelain tiles, cement, grits, etc, and also on wood, glass, metals and plastic;
- unlike paint removers, has a longer application time and more dissolving paint;
- thanks to its viscosity can be easily used on vertical surfaces.

INSTRUCTIONS FOR USE:

It is used pure.

- Always apply on dry surface;
- Apply a uniform layer of PULIGRAFF LIQUIDO with a brush on the surface to be cleaned;
- Let it act from a minimum of a few minutes to 30-60 minutes depending on the type of graffiti to be removed and the amount (e.g. number of layers);
- In the presence of porous media or with accentuated surface roughness it may be useful to make a brushing during the application of PULIGRAFF LIQUIDO;
- Finally, rinse with a pressure washer or manually with a brush or buffers;
- Repeat the application if necessary.

Do not use on synthetic polymer materials (e.g. synthetic agglomerates, methacrylate).

PRECAUTIONS:

- do not use on synthetic polymer materials (e.g. synthetic agglomerates, methacrylate);
- if used on already painted surfaces, check the optimal contact time for removing the graffiti without affecting the painted bottom layer.

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products.
Rev2-Ver040222

WARNINGS:



WARNINGS: DANGER

Hazard statements: Causes serious eye irritation.

Precautionary statements: Wear eye protection / face protection. – If eye irritation persists: Get medical advice / attention. – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. – Keep cool.

UFI: XT10-K00E-G00Y-JA21

Rev2-Ver040222

PACKAGING:

- 1 lt plastic bottle box 6 pcs;
- 5 lt Plastic jerrycan box 4 pcs.

YIELD:

Depending on the absorption of materials:

- approximately 1 lt / 8-12 m2.

TECHNICAL DATA:

- Physical state: colorless dense liquid
- Specific gravity (g/cm3) at 20°C: 1.09
- pH: n.a.
- Flame point (ASTM): >90°C
- Solubility in water: partially soluble.

STORAGE:

Keep the product tightly closed at temperatures between 0 °C and +30 °C and not exposed to sunlight for a long time. The stored product has a useful life of 5 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it