



FUGA PROTETTA

ANTI-DIRT AND ANTI-STAIN TREATMENT FOR CEMENT AND SYNTHETIC JOINTS



User guide

DESCRIPTION:

Dispersion in water of protective fluorinated oil repellents and siloxane oligomers.

FIELDS OF APPLICATION:

For the stain protection protection of cement and synthetic joints.

CHARACTERISTICS:

FUGA PROTETTA is a stain-resistant, dirt-resistant protective material specifically for the treatment of floor joints and wall.

FUGA PROTETTA:

- is a water-based product, odourless, not dangerous and easy to use;
- can be applied on both internal and external surfaces;
- is a stain protection specific for cement and synthetic joints, which eliminates and drastically reduces the absorption capacity of liquid and fatty substances;
- does not form superficial films, is invisible and does not alter the appearance of the material and the color tone over time;
- when used outdoors it gives a strong stain-resistant and self-cleaning protection with rains with a high chemical inertia and resistance to atmospheric agents and trampling;
- is easily re-applied if necessary.

INSTRUCTIONS FOR USE:

- Shake well before use.
- Apply FUGA PROTETTA only on perfectly clean and dry surfaces.
- Spray small amounts of product on the surface and distribute evenly with soft cloth.
- The surface dries in about 10/15 minutes and is walkable.
- Achieves maximum stain protection after about 12 hours.
- During this time avoid washing the surface with water.

PRECAUTIONS:

- FUGA PROTETTA does not have a film-forming function of waterproofing sealant. Therefore, it cannot be used for waterproofing materials subjected to water swing > 10 cm (e.g. swimming pools, pools, etc.);
- does not block the rise of moisture from damp substrates;
- avoid that newly treated surfaces are wet from rain for about 8 hours or more.

NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products.
Rev1-ver310124

WARNINGS:

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements).

VOC (Directive 2004/42/EC): Primer.

VOC expressed in g/litre of product ready for use: 0,00. – Maximum limit: 30,00

PACKAGING:

- 0,75 lt Spray PE – box 6 pcs.

YIELD:

- approximately 750 ml / 30 – 50 m².

TECHNICAL DATA:

- Physical state: opalescent liquid.
- Specific gravity (g/cm3): 1,006.
- pH: 6-7.
- Flame point (ASTM): non-flammable.
- Solubility in water: miscible in water.
- Drying time: 8-12 hours (in ventilated rooms)
- Consolidation time: 48 hours.

STORAGE:

Keep the product tightly closed and at a temperature between 5 and 30 °C in an aerated environment, away from heat sources and not exposed to sunlight for a long time. When stored at low temperatures (<10 °F) the product can become dense, but without affecting its use or performance. The stored product has a useful life of 5 years.

MARBEC SRL

Via Croce Rossa 51
51037 - Montale PT
Italia

CUSTOMER SERVICE

Tel +39 0573959848
Whatsapp +39 3348578502
Email contatti@marbec.it